

Ni-Cd Battery



15 YIL ÖMÜRLÜ BPL SERİSİ TEKNİK VERİLER

15 YEARS LIFE TIME BPL SERIES TECHNICAL DATAS

MODEL	VOLT	Nominal Capacity(Ah) Nominal Kapasite (Ah) 20hour	Ağırlık Weight kg.	Boyutlar Dimensions				Max. Akım Deşarj Discharge Current for 5sec. (A)
				mm.				
				W	D	Load	K.B.Dahil	
BPL 3.3-12	12	3,3	1,35	134	67	60	66	49,5
BPL 7-12	12	7,0	2,60	151	65	93	98	105,0
BPL 7.5-12	12	7,5	2,70	151	65	93	100	112,5
BPL 12-12	12	12,0	4,10	151	98	94	98	180,0
BPL 17-12	12	17,0	6,15	181	76	166	166	255,0
BPL 20-12	12	20,0	6,40	181	76	166	166	300,0
BPL 26-12	12	26,0	9,60	175	166	123	125	390,0
BPL 28-12	12	28,0	9,70	175	166	123	125	420,0
BPL 33-12	12	33,0	11,50	195	129	155	179	495,0
BPL 40-12	12	40,0	14,60	197	165	171	171	600,0
BPL 65-12	12	65,0	22,70	350	166	174	174	650,0
BPL 80-12	12	80,0	26,80	260	168	215	215	800,0
BPL 85-12	12	85,0	31,20	329	172	215	218	800,0
BPL 95-12	12	95,0	33,20	329	172	215	218	800,0
BPL 110-12	12	110,0	40,00	407	173	210	239	800,0
BPL 150-12	12	150,0	51,80	483	171	240	240	800,0
BPL 210-12	12	210,0	73,20	522	240	216	220	800,0

10 YIL ÖMÜRLÜ BPL SERİSİ TEKNİK VERİLER

10 YEARS LIFE TIME BPL SERIES TECHNICAL DATAS

MODEL	VOLT	Nominal Capacity(Ah) Nominal Kapasite (Ah) 20hour	Ağırlık Weight kg.	Boyutlar Dimensions				Max. Akım Deşarj Discharge Current for 5sec. (A)
				mm.				
				W	D	Load	K.B.Dahil	
HR 9-6	6	9,0	1,40	151	34	94	100	120,0
HR 4-12	12	4,0	1,40	134	67	60	66	52,5
HR 5.5-12	12	5,5	1,80	90	70	102	106	75,0
HR 5.8-12	12	5,8	1,88	90	70	102	106	79,5
HR 6-12	12	6,0	2,10	151	51	94	100	82,5
HR 8-12	12	8,0	2,60	151	65	94	100	105,0
HR 9-12	12	9,0	2,75	151	65	94	100	120,0
HR 15-12	12	15,0	4,20	151	98	94	98	180,0
HR 22-12	12	22,0	6,50	181	76	166	166	300,0
HR 33-12	12	33,0	10,00	175	166	123	125	420,0
HR 40-12	12	40,0	12,10	195	129	155	179	495,0
HR 50-12	12	50,0	15,30	197	165	171	171	600,0
HR 75-12	12	75,0	24,75	350	166	174	174	650,0

EUROBAT SERTİFİKALİ AKÜLER EUROBAT CERTIFICATED BATTERIES

En fazla geçerli akım W/hücre, nihai gerilim 1.60, V/hücre + 20°C *Maximum current drain (W/cell) at final voltage 1.60 V/cell at +20 °C*

Type	5min	10min	15min	20min	25min	30min	35min	40min	45min	1h	2h	3h	5h	8h	10h	20h
NP1.2-6/NP1.2-12	6.5	4.7	3.6	3	2.6	2.3	2.1	1.9	1.8	1.4	0.9	0.6	0.4	0.3	0.25	0.12
NP3-6	16.3	11.7	9.22	7.66	6.63	5.83	5.3	4.86	4.47	3.5	2.15	1.57	1.04	0.87	0.63	0.3
NP4-6/NP4-12	21.7	15.5	12.3	10.2	8.8	7.8	7.1	6.5	5.9	4.8	2.9	2.1	1.4	0.96	0.75	0.4
NP7-6/NP7-12	37.9	27.2	21.5	17.9	15.5	13.6	12.4	11.3	10.4	8.4	5	3.7	2.4	1.56	1.27	0.71
NP10-6	54.2	38.9	30.7	25.5	22.1	19.4	17.7	16.2	14.9	12	7.2	5.2	3.4	2.5	1.85	1.2
NP12-6/NP12-12	65.1	46.6	36.9	30.6	26.5	23.3	21.5	19.4	17.8	14.4	8.6	6.3	4.1	2.7	2.25	1.34
NP0.8-12	4.3	3.1	2.4	2	1.8	1.5	1.4	1.3	1.2	1	0.6	0.4	0.3	0.18	0.15	0.08
NP2-12	10.8	7.7	6.1	5.1	4.5	3.9	3.5	3.3	2.9	2.4	1.5	1.2	0.63	0.48	0.37	0.2
NP2.3-12	12.5	9	7	5.8	5.3	4.5	3.9	3.7	3.4	2.7	1.6	1.3	0.7	0.5	0.4	0.2
NP3.2-12	17.4	12.4	9.8	8.1	7	6.3	5.7	5.2	4.8	3.8	2.3	1.7	1.1	0.78	0.58	0.33
NP17-12I	92.1	66.1	52.2	43.4	37.6	33	30	27.5	25.4	20.4	12.2	8.8	5.9	4.1	3.1	1.74
NP24-12/NPL24-12I	130	93.2	73.8	61.3	53.1	46.6	42.4	38.9	35.8	28.8	17.3	12.6	8.3	5.76	4.53	2.5
NP38-12/NPL38-12I	206	148	117	97.1	84.1	73.8	67.1	61.6	56.6	45.6	27.4	19.9	13.1	9.22	7.9	3.84
NP65-12/NPL65-12I	352	253	200	166	144	126	115	105	96.9	78.1	46.9	34.1	22.5	15.7	12	6.5
NPL78-12IFR	423	303	240	199	172	152	138	126	116	93.7	93.7	40.9	27			
NPL100-12	542	388	307	255	221	194	176	162	149	130	72	52	34			
NPL130-6FR	705	505	400	332	287	253	230	211	194	156	93.7	68.1	45			
NPL200-6	1084	777	615	510	442	388	353	324	298	240	144	105	70			

Güç (Watt) 20°C'de 1.6V nihai gerilim için hücre başına deşarj *Discharge power (Watt) per cell for final voltage of 1.6V at 20°C*

Akü türü Type of Battery	Autonomy Özerklik				Minutes Dakika						Hours Saat									
	3	5	6	10	15	20	30	40	50	60	1.5	2	2.5	3	4	5	6	10	15	20
SWL750	239	196	179	128	105	87.5	66.3	51.5	42.4	38.0	28.3	23.1	18.6	15.7	11.8	9.68	8.08	5.83	4.01	3.06
SWL1100	346	285	263	200	160	129	94.0	77.8	67.0	58.7	42.7	33.7	28.0	24.2	18.8	15.8	13.7	9.67	6.64	5.08
SWL1800	553	476	440	329	257	213	160	128	108	92.8	65.3	51.8	44.0	38.5	30.9	25.3	21.3	13.1	9.12	7.05
SWL1850	536	453	420	319	254	210	153	125	109	96.3	70.0	54.2	45.2	39.7	31.7	27.0	23.3	16.3	11.2	8.56
SWL2250	582	524	492	375	307	251	182	149	128	112	82.7	65.9	54.9	48.2	38.5	32.8	28.4	19.9	13.6	10.4
SWL2300	661	571	513	411	329	266	207	165	139	119	83.9	65.3	54.3	46.2	36.4	30.4	26.1	16.2	11.1	8.56
SWL2500	751	649	583	490	373	303	236	188	158	135	95.3	74.2	61.7	53.7	42.3	35.3	30.3	19.3	13.2	10.0
SWL1850-6	494	481	474	448	416	384	273	229	201	177	135	107	89.5	78.6	62.8	53.5	46.1	32.3	22.2	17.0

Güç (Watt) 20 °C'de 1.65V nihai gerilim için hücre başına deşarj *Discharge power (Watt) per cell for final voltage of 1.65V at 20°C*

Akü türü Type of Battery	Autonomy Özerklik				Minutes Dakika						Hours Saat									
	3	5	6	10	15	20	30	40	50	60	1.5	2	2.5	3	4	5	6	10	15	20
SWL750	229	191	176	127	105	87.3	66.2	51.2	42.2	37.8	28.2	23.0	18.5	15.6	11.7	9.53	7.92	5.67	3.89	2.98
SWL1100	331	276	256	196	158	128	93.5	77.3	66.7	58.2	42.2	33.3	27.7	24.0	18.5	15.5	13.5	9.33	6.41	4.90
SWL1800	530	458	424	322	256	211	158	127	107	92.3	64.8	51.5	43.8	38.3	30.7	25.2	21.2	13.0	9.05	6.98
SWL1850	511	437	411	318	252	209	153	125	109	95.5	69.7	53.7	44.7	39.3	31.3	26.7	23.0	16.0	11.0	8.40
SWL2250	578	517	483	370	305	249	180	148	127	111	82.3	65.3	54.3	47.8	38.1	32.4	28.0	19.5	13.4	10.2
SWL2300	645	532	494	400	326	266	205	164	137	116	81.7	64.6	54.1	45.9	36.3	30.3	26.0	16.2	11.1	8.56
SWL2500	733	605	562	477	370	302	233	186	155	132	92.9	73.4	61.5	53.4	42.2	35.2	30.2	19.3	13.2	10.0
SWL1850-6	494	481	474	448	416	384	272	228	200	175	134	106	88.5	77.8	62.0	52.9	45.5	31.7	21.8	16.6

Güç (Watt) 20 °C'de 1.7V nihai gerilim için hücre başına deşarj *Discharge power (Watt) per cell for final voltage of 1.7V at 20°C*

Akü türü Type of Battery	Autonomy Özerklik				Minutes Dakika						Hours Saat									
	3	5	6	10	15	20	30	40	50	60	1.5	2	2.5	3	4	5	6	10	15	20
SWL750	217	183	168	124	103	86.7	65.8	50.8	42.1	37.6	28.0	22.9	18.4	15.5	11.5	9.44	7.83	5.58	3.83	2.93
SWL1100	314	264	245	190	154	127	93.2	77.0	66.3	57.5	41.8	32.8	27.3	23.8	18.3	15.3	13.3	9.00	6.18	4.73
SWL1800	504	431	401	312	253	210	157	126	106	91.8	64.5	51.3	43.7	38.2	30.6	25.0	21.0	12.9	9.00	6.93
SWL1850	489	437	405	313	247	209	153	124	108	94.7	69.3	53.3	44.3	39.0	31.0	26.3	22.7	15.7	10.8	8.24
SWL2250	565	497	463	359	300	248	177	146	126	110	81.9	64.9	53.9	47.4	37.7	32.0	27.6	19.1	13.1	10.0
SWL2300	598	500	480	380	320	263	197	159	132	115	81.5	64.5	53.9	45.8	36.3	30.1	26.0	16.2	11.1	8.56
SWL2500	680	568	545	453	363	299	223	180	150	131	92.7	73.3	61.3	53.2	42.2	35.0	30.2	19.3	13.2	10.0
SWL1850-6	492	479	472	447	415	383	272	227	199	174	133	106	87.7	77.2	61.4	52.1	44.9	31.1	21.3	16.3